

Installation Instructions



Hostel Shoppe Euro Seat Bag

© www.hostelshoppe.com

Updated: 1/9/2009



1. Install Seat Trim

The sharp edge of most composite seats can eventually wear through the fabric on your new Euro Seat Bag. Some seats have a rubber or plastic trim piece already installed to protect your bag.



2. Slide Bag Over Seat

Slide the mesh pocket of the seat bag over the seat shell and foam / fabric pad. Make sure the seat pad is even with or slightly above the top of the seat shell (this will help to keep the mesh away from the seat shell).



3. Pull Bag Tight

Center the seat bag and pull it down tight. The seat should fill up the top of the mesh bag pocket completely.



4. Adjust Cinch Strap

Inside the bladder pocket at the bottom of the bag there is a cinch strap to snug the base of the seat bag around the seat. Tighten it until the seat pad is slightly compressed.



5. Stabilizer Strap Installation

With a loaded bag over bumpy roads the rounded and tapered seat shape can cause your seat bag to shift and creep. We've designed special hook/loop stabilizer straps to secure your load and keep your bag from moving around.

Be sure to clean the attachment section of your seat with rubbing alcohol to ensure that the adhesive Velcro sticks.

Installation is easiest if you leave the hook and loop sections fastened together. Remove the protective film from the adhesive-backed hook.



6. Apply Straps to Seat

Pull the stabilizer strap tight, but not so tight that the seat bag shifts on the seat. Line up the adhesive backed section with the outside of the seat rib and press it on firmly. Repeat steps 5 and 6 for the other side of the seat.

Now... GO RIDE!